

SASI600

Airborne Hyperspectral SWIR Imager (0.95 – 2.45 microns)

100 Spectral Channels

40° FOV, 600 Spatial Imaging Pixels

Internally Cooled to Low Temperature – Low Noise

Continuous VNIR – SWIR Coverage w CASI-1500

Custom diffraction-limited, high-performance optics¹



HYPER SPECTRAL & THERMAL REMOTE SENSING

¹Diffraction-limited optics ensure that every pixel is a spatially independent sample with no smearing. This gives users optimal image quality and focus.

SASI600

Synthetic Target Mapping / Classifications / Geological Exploration / Vegetation Speciation / Aquatic Pollution Presence / Pipeline Corridor Mapping / Mineral Composition

SENSOR TYPE

SWIR Pushbroom Sensor
(Shortwave infrared Airborne Spectrographic Imager)

PERFORMANCE

Spectral Range (Continuous Coverage)	950-2450nm
# Spectral Channels	100
# Across-Track Pixels	600
Total Field of View	40 degrees
IFOV	1.2 mRad
f/#	f/2.0
Spectral Width Sampling/Row	15nm average
Spectral Resolution (FWHM)	15nm average
Pixel Size	30 x 30 microns
Dynamic Range	14-bits (16384:1)
Sustained Data Rate, Mpix/Second	6.0 Mpix/sec
Spectral Smile/Keystone Distortion	±0.25 pixels
Peak Signal to Noise Ratio	SNR models for various radiance conditions are available

SASI-600 Imagery:



DIMENSIONS, WEIGHTS, AND POWER

ITEM	W / H / D (CM) / WT. (KG)
SHU	85.0 / 20.0 / 50.0 / 40
ICU	48.3 / 17.8 / 52.3 / 16
Display	34.0 / 26.0 / 7.0 / 1.7
SHU Cable Length	3 metres
Power	24-32 VDC, 10A VDC

ENVIRONMENTAL CONSTRAINTS

Operating Temperature	Ambient 0 to +35°C (+32 to +104°F) RH 20-80% non-condensing
Maximum Altitude	3,048m (10,000 ft) ASL (unpressurized, non-condensing environment)
Storage Temperature	Optimum -20 to +60°C (-4 to +120°F) RH 10-90% non-condensing

OPERATION

Display	15" sunlight-readable, 1024x768 resolution. High altitude display available
Operator	Control Via keyboard, Windows™ OS
Real-Time Display	Scene Image, automated sensor health diagnostics, signal level display
Remote Diagnostics	Ethernet-ready remote diagnostic capability on ICU
Data Storage	Swappable mass storage
Multiple Sensor Operation	Up to 5 ITRES imagers may be simultaneously operated via MuSIC™ System

DATA PROCESSING SYSTEM

- Processing software Linux and Windows-based
- Playback software (Quicklook)
- Generates 16-bit BIP format data compatible with ENVI (BIL, BSQ formats possible)
- ASCII format ancillary QC data output – clocking, attitude, logging, GPS, and sensor health monitoring information
- Outputs diagnostic information
- Selectable band output

GEOCORRECTION SYSTEM

- GPS/IMU integration to POS AV (other systems available)
- Data synchronization (GPS, attitude, and image streams)
- Precision positional accuracy
- Bundle adjustment software (no need for GCPs)
- Stabilized mount option

GEOCORRECTION/ORTHO CORRECTION/MOSAICKING SOFTWARE

- Best nadir pixel selection function during mosaicking
- Accepts Lidar, Ifsar, and USGS DEM inputs
- Nearest neighbor algorithm used – maintains radiometric fidelity
- Separately stores ancillary data (e.g. pointing vector, DEM)

HOURLY COVERAGE (35% SIDELAP)

- Over 70 km² at one meter spatial resolution

SPATIAL RESOLUTION & FLIGHT ALTITUDE

- Resolutions between 1 m to 3.5 m possible with typical unpressurized aircraft at 110 knots
- 1m Pixel Example: Flight altitude = 2704 ft AGL, air speed = 110 knots

ITRES Research Limited

Calgary, Alberta, Canada
T: +1.403.250.9944
F: +1.403.250.9916

USA Contact Information
T: +1.228.467.2345
TF: +1.877.250.9944

info@itres.com
www.itres.com

Document ID: U10034-03
© 2010 ITRES Research Ltd

All ITRES sensors are calibrated to traceable standards. Specifications subject to change without notice.